

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY)		2. REPORT TYPE Technical Papers		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER 3058	
				5e. TASK NUMBER RF9A	
				5f. WORK UNIT NUMBER	
				8. PERFORMING ORGANIZATION REPORT	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/PRS 5 Pollux Drive Edwards AFB CA 93524-7048				10. SPONSOR/MONITOR'S ACRONYM(S)	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/PRS 5 Pollux Drive Edwards AFB CA 93524-7048				11. SPONSOR/MONITOR'S NUMBER(S)	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
20030123 038					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE	A		Leilani Richardson
Unclassified	Unclassified	Unclassified			19b. TELEPHONE NUMBER (include area code) (661) 275-5015

Standard Form 298 (Rev. 8-98)
Prescribed by ANSI Std. Z39.18

21 separate items enclosed

NOTIFIED/FILE

3055 PF9A

MEMORANDUM FOR PR (In-House Publication)

FROM: PROI (TI) (STINFO)

30 November 1999

SUBJECT: Authorization for Release of Technical Information, Control Number: **AFRL-PR-ED-TP-1999-0227**
Talley, D., "Overview of Pulse Detonation Engines" (BF1)

49th JANNAF Propulsion Meeting (Tucson, AZ, 14-16 Dec 1999)

(Statement A)



BRIEFING FOR INDUSTRY 16 Dec 1999



Overview of Pulse Detonation Engines

Doug Talley
Air Force Research Laboratory|AFRL
AFRL/PRSA, 10 E. Saturn Blvd.
Edwards AFB, CA 93524-7660
(805)275-6174
Douglas.Talley@ple.af.mil


— Air Force Research Laboratory|AFRL —

6.2 Objectives

Assess the technical merit of the pulsed detonation cycle and, if appropriate, develop pulsed detonation propulsion technology for Air Force applications.

	<u>FY98</u>	<u>FY99</u>	<u>FY00</u>	<u>FY01</u>
Funding (\$1,000's)				
Edwards	810	309	309	309
WPAFB		731	298	298


The Pulsed Detonation Cycle



The Potential

- Better Isp
- Higher thrust/weight (reduced feed pressures lead to lighter pumps)
- Deeply throttleable and scalable (multiple tubes, operating frequency)
- Lower cost / more reliable (less complex)
- Wider applicable Mach number range

Const. vol. estimate of Isp in comparison to a CP device operating at the same fill pressure (compares equivalent feed systems).



The Issues

- Ignition energy
- Deflagration-to-detonation transition (minimize DDT length)
- Practical fuels (JP, RP)
- Multiphase ignitions
- Oxygen enrichment
- Preignitions
- Thermal loads
- Vibration and cycle fatigue
- Valves/injectors

Rocket - Specific Issues

- Filling in a vacuum
- Issues arising out of also having to inject an oxidizer
 - Different mixing regimes
 - Mixing and detonation of TWO condensed phases
- Different kinetic and rheological properties
 - Wide range of possible fuel/oxidants
 - Low/high temperature space environment
 - Lack of emphasis on emissions
- Higher rocket combustion temperatures
 - Hotter walls promote pre-detonation ?

Technical Approach

- Develop/use/oversee models of pulsed detonation processes
 - Ideal cases; limiting cases
 - Cycle decks
 - High fidelity models
- Experimentally assess the performance of in-house and proprietary pulsed detonation systems.
 - State of the art facilities
- Conduct in house *public domain* research and development
 - ITAR restrictions could apply

Strategic Alliances




Government	Industry	Academia
<ul style="list-style-type: none">• NASA<ul style="list-style-type: none">- Revcon- MSFC programs• NAVY<ul style="list-style-type: none">- MURI- 6.2• SBIR funding	<ul style="list-style-type: none">• APRI• ASI• Boeing• Enigmatics• GE• HyPerComp• Lockheed/Martin• MSE• RR/Allison• SAIC• UTRC/P&W	<ul style="list-style-type: none">• Cal Tech• NPS• Penn State• Princeton• Stanford• UCSD• U. Florida• U. Texas



Hot fire facility for PDRE testing at Edwards AFB

Fuel	H ₂ (g), CH ₄ (g)
Oxidizer	O ₂ (g)
Purge gas	N ₂ (g), He(g)
H ₂ mass flow rate	.15 lbm/s (.07 Kg/s)
CH ₄ mass flow rate	.25 lbm/s (.11 Kg/s)
O ₂ mass flow rate	1.0 lbm/s (.45 Kg/s)
N ₂ mass flow rate	.5 lbm/s (.23 Kg/s)
Water flow rate	16 lbm/s (7 Kg/s)
Max. system press.	2640 psi. (179 atm)

128 ch, 200 kbs scanning A/D
 16 ch, 2 MHz per ch A/D, independently controlled
 Central laser/optics room
 Fully instrumented PDRE DAQ and control system




PDE Research Engine at WPAFB GM Quad 4 DOHC, 4 Cylinder Pulsed Detonation Engine



- Adapter Plate Mounts Detonation Tubes
 1-4 Tubes
 2" Diameter PDE Tubes for R&D
 3 1/2" Diameter PDE Tubes for Engine
- Electric Motor Driven Camshafts
 0.5-50 Hz currently (per tube)
 100 Hz possible
- Vapor Fuels: Hydrogen and Propane
- Liquid FI: Gasoline, Ethanol, JP, etc.

- Junkyard Technology - \$2,000 Hardware Investment
- Pontiac Grand Am Cylinder head (formerly 150 BHP) produces up to 3,000 lbf theoretical thrust as PDE
- Test-bed for PDE Research, Benchmarking
- Predetonator/Initiator Development
- High Frequency Operation
- Multi-tube Effects Pulsed Ejector Research



Stock Intake
 Manifold with Ball
 Valve Selection of
 1-4 Detonation
 Tubes
 (Purge Manifold
 Similar)

FY99 Accomplishments


- Demonstrated contractor capability to build a back pressure with multiple tubes discharging into a common nozzle
 - Joint effort with Adroit Systems, Inc, and NASA
- Developed constant volume limit model
- Initiated study on the use of condensed phases in PDRE's, including monopropellants
- Initiated efforts to establish a panel to develop a community-standard PDE/RE performance methodology
- PRS-East accomplishments

AFRL Constant Volume Code

Features

- Various propellants, variable mixture ratios
- Gaseous phase and liquid phase propellants
- Buffer gases and partial fills
- Nozzle options
 - Fixed area ratio nozzles
 - Area ratios continuously adjust to match pressure ratios during blowdown
 - Separated or non-separated flow
- Calculates Isp, average thrust, peak pressures, blow down times, area ratios, etc.

Effect of Ambient Pressure on Specific Impulse



GOX/GH2, MR=2.25
Complete expansion to ambient
5 atm fill pressure
Isentropic blow down

Theoretical result for
expansion at infinite
expansion ratio to a vacuum


$$\frac{I_{sp,CV}}{I_{sp,CP}} = \frac{2}{\gamma + 1} \left(\frac{T_{CV}}{T_{CP}} \right)^{1/2} < 1$$

$$< (T_{CV} / T_{CP}) < \gamma$$

*placement
of symbols -*

Multi-cycle operation

$$V_{chamber} = 10 \text{ cm}^3 \quad V_{fuel} = 1 \text{ cm}^3 \quad \text{frequency} = 100 \text{ Hz}$$




Combustion/Detonation Modeling

Dr. Vish Katta
(ISSI)
PRSC in-house
contractor




AFRL/PRSC Detonation Modeling

- Currently one of two groups in the US modeling deflagration to detonation transition (DDT)
- Initiation and DDT Studies
- Detonation Propagation
- Confinement/Obstructions
- Shock Reflections



Detonation Propagation (direction is right to left)

Reflecting and coalescing transverse waves are the mechanism responsible for propagation of detonation from small tube (i.e. predetonator) to bigger tube




Peak Pressure or 'Smoke Foil' Traces with Particle Traces
(direction is right to left)


— Air Force Research Laboratory AFRL —

Successful Firing of 4-Tube AFRL Research PDE

Photo of firing



Pressure traces in a single tube



Signal (V) vs time

— Air Force Research Laboratory|AFRL —

Planned for FY00

- Facilitate JANNAF panel to oversee the development of a community standard PDE/RE performance model
- Demonstrate vacuum start of a multi-tube, common nozzle PDRE
 - Continuation of Adroit/NASA work
- Determine the feasibility of a "constant-volume combustion" pulsed engine operating on condensed phase propellants
 - Monopropellants and bipropellants
- PRS-East plans

— Air Force Research Laboratory|AFRL —

Videotapes

← ?
Have these
been
approved?

Summary

- Significant facility upgrades have been installed at to support PDE/RE development and evaluation and demonstrated
 - PDRE development and firings at Edwards AFB
 - PDE development and firings at WPAFB
- Modeling efforts are underway in-house to support PDE/RE development
 - Constant volume code
 - Condensed phase code
 - DDT code
 - Other PRS-East codes
- AFRL is attempting to facilitate a panel to oversee the development of a community standard PDE/RE performance model

*something
missing*